



KM-340M_H

SLIM-LINE MODULAR CRESCENT CUBER



KM-340M_H
1/18/16
Item # 13344

Ice Machine Dimensions
W x D x H
22" x 27^{3/8}" x 30^{5/16}"



KM-340MAH ★

Air-Cooled 1 Phase
Shown on optional Bin: B-300

KM-340MWH

Water-Cooled 1 Phase



Item #: _____
Project: _____
Qty: _____
AIA#: _____

Features

- ▶ Individual crescent cube
- ▶ Stainless steel evaporator
- ▶ CycleSaver™ design

- Up to 387 lbs. of ice production per 24 hours
- Durable stainless steel exterior
- Protected by H-Guard Plus Antimicrobial Agent
- EverCheck™ alert system
- Removable air filters (Air-cooled model only)
- R-404A Refrigerant

Available on Bins:

B-250 B-800 B-1500SS
B-300 B-900 B-1650SS
B-500 B-1150SS
B-700 B-1300SS

Available on Dispensers:


DB-130H
DB-200H
DM-200B

Warranty:

3 Year Parts & Labor on entire machine. 5 Year Parts & Labor on Evaporator. 5 Year Parts on Compressor; air-cooled condenser coil.
Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

Condenser	Model	ICE PRODUCTION		Per Cycle		WATER USAGE		ELECTRICAL				Heat Rejection BTU/hr.	Shipping Weight	ENERGY STAR®
		Air / Water Temp Lbs. per 24 hours	70°/ 50°F	90°/ 70°F	Lbs.	Cubes	Potable Gal. per 100 lbs.	Condenser Gal. per 100 lbs.	kWh Used per 100 lbs.	Max. Fuse Size or HACR Circuit Breaker	Amperage			
Air-Cooled	KM-340MAH	387	325	11.3	480	20.0	N/A	5.9	20A	9.7A	115V/60/1	6,700	153 lbs.	★
Water-Cooled	KM-340MWH	386	360	11.3	480	20.5	115	4.9	20A	7.4A	115V/60/1	7,500	175 lbs.	

KM Cube Dimensions*



* approximate size; image not to scale

Operating Limits

- Ambient Temp Range 45 - 100°F
- Water Temp Range 45 - 90°F
- Water Pressure 10 - 113 PSIG
- Voltage Range 104 - 127V

Service

- Panels easily removed and all components accessible for service.
- Removable/cleanable air filters. (Air-Cooled model only)
- Allow 6" (15 cm) clearance at rear, sides, and top for proper air circulation and ease of maintenance/service.

Plumbing

- Icemaker Water Supply Line: Minimum 1/4" Nominal ID Copper Water Tubing or Equivalent
- Icemaker Drain Line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent
- Water-Cooled Model (Lines Must Be Independent of Icemaker)
- Condenser Water Supply Line: Minimum 1/4" Nominal ID Copper Water Tubing or Equivalent
- Condenser Drain/Return Line: Minimum 1/4" Nominal ID Hard Pipe (open drain system) or Copper Water Tubing (closed loop system) or Equivalent

Hoshizaki reserves the right to change specifications without notice.




KM-340M_H




KM-340M_H
1/18/16
Item # 13344

SLIM-LINE MODULAR CRESCENT CUBER

FRONT VIEW




AIR-COOLED




WATER-COOLED

SIDE VIEW




AIR-COOLED




WATER-COOLED

BACK VIEW




AIR-COOLED




WATER-COOLED

BOTTOM VIEW



AIR-COOLED



WATER-COOLED